

YHPCConnect

AUTOMATIC 1 END INSERT HOUSING & CRIMPING MC YHPC-SK-A16-A

AWG 30 ~ 18

12 Different Colours Of Same Wire Size x 2 Layers

Min. Cut Length 45 mm



YHPC-SK-B06
Servo Motor 2.5T
Crimp & Programmable
Crimp Height Mc



Features

1. Using Schneider brand servo motors to provide precision, efficient and stability..
2. Using touch screen touch adjustment, including: wire length, strip length, half strip length, insert terminal into housing position depth, file setting storage all within a touch.
3. Adopt advanced quality inspection system in terms of crimp force monitoring, terminal insert housing and CCD vision system detection onto wire position and condition on terminal.
4. Adopt advanced fault removal system and auto detect low air pressure, motor abnormality, belt abnormality. It can automatic stop the machine and show the causes of abnormality.
5. The best features include using the YHPC-SK-B06, Servor Motor Crimp mc where crimp height is programmable thereby simple adjustment, short adjustment time thus greatly reduce set-up time.
6. Using touch screen to adjusts crimp height of the terminal is more precise and stable

YHPC CONNECT | BLK. 478C ,YISHUN STREET 44, #09-161 SINGAPORE 763478 |

H/P:+65-91293768 | E-MAIL: yhpc99@gmail.com

WeChat ID : PCLeeJUL1962 | WhatsApp ID : YHPC-PCLee |

WEBSITE: www.technocore.com.sg | CONTACT PERSON – LEE PENG CHAI

AUTOMATIC 1 END INSERT HOUSING & CRIMPING MC YHPC-SK-A16-A

Technical Data

Model	YHPC-SK-A16-A
Functions	Cut, 1 or 2 sides strip, 1 crimp & insert housing (2 layers) , 1 side half strip & crimp
Wire Colour	12 Different colours of same wire size for 2 layers
Wire Size	AWG 30 ~ 18
Capacity	1000 pcs. / hr. (Depend on wire material)
Cut Length	45 mm – 3000 mm
Cutting Accuracy	1 mm + Cut Length x 0.1% below
Stripping Length	0 ~ 7 mm
Twist Length	3mm – 7mm
Tin Length	0.5mm – 7mm
Crimp Machine	YHPC-SK-B06, Servo Motor 2.5T Crimp & Programmable Crimp Height Mc x 2 units Standard 30 mm stroke can modify to 40mm upon request.
Detector	Crimp Force Monitoring, CCD terminal appearance detection system, terminal plug and pull force detection, detection of wire, terminal and housing availability.
Air Pressure	5 ~ 6 kgf/cm², Use Dry Clean Air
Power Source	AC Single Phase,200/220V(within±10%) 50 Hz ,15.1 A **True Ground required. Can modify to 110v upon request
Dimension/Mass	190L x 92W x 162H(cm) / Kgs
Country Of Origin	China

YHPC CONNECT | BLK. 478C ,YISHUN STREET 44, #09-161 SINGAPORE 763478 |

H/P:+65-91293768 | E-MAIL: yhpc99@gmail.com

WeChat ID : PCLeeJUL1962 WhatsApp ID : YHPC-PCLee |

WEBSITE: www.technocore.com.sg CONTACT PERSON – LEE PENG CHAI