



YHPConnect

AUTOMATIC HIGH PRODUCTION SINGLE END CRIMP & TIN M/C YHPC-SK-A18

Shortest 8.0 mm cut
length



Features

- 1) Develop own Patent Right technology for cut and strip.
- 2) Using Japanese brand for the Servo Motor and SMC brand for the Pneumatic Component thereby able to provide better Accuracy, Efficiency and Stability.
- 3) Touch screen touch adjustment, including: Wire Cut Length, Strip Length, Half-Strip Length, Twist Tension, Twist Length and Tin Length.
- 4) The use of computer-based automatic detection, that detect for Low Air Pressure, Motor Abnormalities and Abnormal Belt. Upon detect of error, it will automatically shut down, and will show the cause of the fault.
- 5) PVC waste is sucked into a waste collection bag.
- 6) Quick set-up applicator.

YHPC CONNECT | BLK. 478C ,YISHUN STREET 44, #09-161 SINGAPORE 763478 |

H/P: +65-91293768 | E-MAIL: pclee@singnet.com.sg / yhpc99@gmail.com

WEBSITE: www.technocore.com.sg | CONTACT PERSON – LEE PENG CHAI |

AUTOMATIC HIGH PRODUCTION SINGLE END CRIMP & TIN M/C YHPC-SK-A18

TECHNICAL DATA

Model	YHPC-SK-A18
Function	Crimp 1 side, Twist and Tin the other side. (Depend on wire size, maximum can process 4 wires at one time.)
Capacity	6000 Pieces./ Hour (Depend on material)
Wire Size	Awg 32 ~ 20
Strip length for Crimp	0 ~ 7.0 mm
Twist Length	3 ~ 7.0 mm
Tin Length	0.5 ~ 7.0 mm
Cut Length	8.0 ~ 350.0 mm (Optional for 351.0 ~ 1000 mm)
Cut Length Accuracy	Cut length below 100 mm: +(0.5 + wire length X 0.002) mm Cut length above 100 mm: +(1.0 + wire length X 0.002) mm
Press Capacity	1.5 TON , FREQUENCY INVERTER MOTOR
Applicator	OTP / JAM EQUIVALENT, SIDE OR END-FEED.
Stroke Length	30 mm
Detector	Pressure down, Crimp error, Wire load & No Wire.
Air Pressure	5 ~ 6 kgf/cm ² , Use Clean & Dry Air
Power Source	220V(within±10%) 50/60 Hz , 10 A, Single Phase, True Earth Can do 110V upon request.
Dimension/Mass	180L x 70W x 220H(cm) / 340 Kgs
Packing Dimension	x x (cm) / Kgs
Packing Include	(3 sets of cut & strip blades) + (1 sets of wire guide pipes, Ø1.0,1.5,2.0,2.5 & 3.0) + (Paper Winder) + (1 Applicator)
Country Of Origin	CHINA
Optional	Crimp Force Monitor, SOLTEC , CFM-SOL10 (Single Channel)
Optional	4 Bobbin Wire Sender, SK-B01