

SERVO MOTOR 2.5T CRIMP & PROGRAMMABLE CRIMP HEIGHT MC

YHPC-SK-B06



Features

Auto paper winder

Soltec
Crimp force monitor

Dual language
touch screen
(English & Chinese)

No terminal and
terminal tension
detector

Features

Crimp height
programmable thru
operation panel with
storage file (up to 20)

30mm ~ 40mm stroke
(selectable thru switch)

Standard : for
OTP / JAM applicator.
Option: Can do for other
applicator

Programmable Stroke Speed

YHPC CONNECT | BLK. 478C ,YISHUN STREET 44, #09-161 SINGAPORE 763478 |

H/P:+65-96196415 | E-MAIL:pcee@singnet.com.sg

WEBSITE:www.technocore.com.sg | CONTACT PERSON – LEE PENG CHAI |

SERVO MOTOR 2.5T CRIMP & PROGRAMMABLE CRIMP HEIGHT MC

YHPC-SK-B06

Technical Data

Model	YHPC-SK-B06
Functions	Single-end crimp and programmable crimp height, speed adjustable
Crimp Capacity	24,500N (2.5 tons equivalent) Servo press X 1 unit
Stroke Length	30mm ~ 40 mm (selectable thru a switch)
Applicator	Standard : OTP / JAM type with quick fix base pate. Option: can made to suit other types of applicator, change rambolt & base plate
Crimp Accuracy	0.01 mm
Detector	.No terminal and terminal tension, Crimp Force Monitoring.
Power Source	AC Single Phase, 200/220V(within±10%) 50 Hz ,3.2 A
Dimension/Mass	60L x 40W x 65H(cm) / Kgs
Items Included	Paper Winder, Soltec Crimp Force Monitor, Safety Footswitch, power Cord and Tool Box.
Country Of Origin	China